

Hammer drills – Exceptional performance

**Power through
concrete + stone**



- Optimum drilling performance
- Robust design and galvanised surfaces ensure long service life
- Grip, cylinder and casings are made from cast stainless steel
- Air buffer minimises component wear during standby operation
- From model BH 11 available with power blowing system for blowing out the drill hole

	Model	Blow frequency per min	Air demand *) m³/min	Chuck – Shank		Weight kg	Impact force Nm	Weighted sum acceleration value **) m/s²
Grip	BH 8	3660	0.6	○S 19 x 82.5	a)	10.0	10	13.1
	BH 8	3660	0.6	○S 22 x 82.5	a)	8.6	10	13.1
	BH 11	2910	1.4	○S 22 x 108	b)	15.5	24	20.0
T-grip	BH 16	2400	1.9	○S 22 x 108	b)	18.9	31	20.3
	BH 21	2740	2.1	○S 22 x 108	b)	23.9	50	23.1
T-grip (vibration damped)	BH 16 V	2440	1.9	○S 22 x 108	b)	22.9	31	4.8

*) at 5 bar **) As per ISO8662 a) = Retaining spring b) = Retaining cap
Applicable drill sets are available separately: mono-block drill, chuck, drill bit



Built for a Lifetime!

KAESER COMPRESSORS Australia Pty. Ltd.
 Locked Bag 1406 – Dandenong South – Vic. 3164
 45 Zenith Road – Dandenong – Vic. 3175
 Phone: +61 3 9791 5999 – Fax: +61 3 9791 5733
 www.kaeser.com – E-mail: air@kaeser.com.au